



CHDR

Centre for Human Drug Research

INVESTIGATIONAL BROCHURE DE-RISK INSTALL INSTRUCTION

Version: 1.0

Contact: tom@vansteinengroentjes.nl

Installing Investigational Brochure De-risk tool

To install the ib-derisk tool on your own server, make sure you copy the contents of the archive into the public folder of a Linux, Apache, MySQL, PHP (LAMP) stack.

Specific version requirements

Apache needs a couple of libraries (that on most LAMP stacks are enabled by default). These are:

- mod_php5
- mod_rewrite
- mod_expires
- mod_deflate
- mod_filter
- mod_ext_filter

MySQL >= 5.5

PHP >= 5.6

PHP needs to have **PDO** and **gettext** enabled (most installs have these enabled by default).

Once copied to the public html folder, create a database with your preferred database name and run the provided SQL queries from the *ib-deriskInstall.sql* file in the new database. This will create all the necessary tables and inserts the data required.

Next, edit the file **/config/config.php**

In this file add the URL, Database info, and SMTP credentials. All necessary information is marked with a comment starting with */* PROVIDE ... */*

You are done installing the tool on the server!

When you navigate to the main url of the just installed software, you will see the login page.

The default username is **Admin** and the default admin password is **Password1**.

Please change this after the first login.

SSL

If you want to use a secure SSL connection, remove the “#” on line 19 of the *.htaccess* file in the root folder.

In case you also want to force the *www* tag you can remove the hash tags (#) at the lines 21 and 22 too.

If you use SSL make sure you provide the *SITE_ROOT* value in the *config.php* file starting with *https://*.

LOG

The tool has the possibility to log certain actions and errors to the database. The tables for the log are not included in the *ib-deriskInstall.sql* file. They are available upon request.

CREATE NEW ADMIN ACCOUNTS

To mark another account as admin, the database administrator has to log into the database and flip the flag in the *user_accounts* table from 0 to 1 in the *admin* column.